

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

VERSATEX CELLULAR PVC TRIMBOARDS

MANUFACTURED BY

VERSATEX BUILDING PRODUCTS

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC-700 NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.

Michael Luzier – President & CEO

April 23, 2010

March 31, 2023

CERTIFICATE #000128

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000128

Products: Versatex Cellular PVC Trimboards

Manufacturer: Versatex Building Products

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2012 NATIONAL GREEN BUILDING STANDARD				
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points	
2012 NGBS 601.7	Building materials/assemblies do not require additional site applied material for finishing. 12 points max. awarded.	1,2,5	For 5 points, 90% or more of the installed exterior trim must be this product. For 2 points, 50-90% of the installed exterior trim must be this product. For 1 point at least 35% of the installed exterior trim must be this product.	

2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite-resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in conjunction with other termite-resistant materials for the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use with other termite-resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.
----------------------	---	-----	--

2015 NATIONAL GREEN BUILDING STANDARD				
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS	
2015 NGBS 601.7	Prefinished building materials or assemblies listed below have no additional site-applied finishing material are installed.	1,2,5	For 5 points, 90% or more of the installed exterior trim must be this product. For 2 points, 50-90% of the installed exterior trim must be this product. For 1 point, at least 35% of the installed exterior trim must be this product.	
2015 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite-resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in conjunction with other termite-resistant materials for the first 3 feet in moderate to heavy termite zones, and six points are awarded for use with other termite-resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.	

2020 NATIONAL GREEN BUILDING STANDARD				
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points	
2020 NGBS 601.7	Prefinished building materials or assemblies listed	1, 2, 5	For 5 points, 90% or more of the installed exterior trim must be this product. For 2 points, 50-90% of the installed exterior trim must be this product. For 1 point, at least 35% of the installed exterior trim must be this product.	
2020 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite-resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in conjunction with other termite-resistant materials for the first 3 feet in moderate to heavy termite zones, and six points are awarded for use with other termite-resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.	